

POLYSAFE VOGUE ULTRA

- BRE Global A+ Rated Product (Certificate No: ENP 336)
- A range of 12 decorative colours with co-ordinating chip and special surface finish
- Coloured quartz, aluminium oxide and silicon carbide particles incorporated throughout the full thickness of the vinyl to improve traction and safety underfoot

SPECIFICATION



2.0mm



2m x 20m = 40m²



2400g/m²



GENERAL PERFORMANCE

EN 13845

ASTM F1303

Agreement – G5ws



REACTION TO FIRE

EN 13501-1 Class Bfl-S1

{ EN ISO 9239-1 ≥8kw/m²
EN ISO 11925-2 Pass

ASTM E648 Class 1



ENHANCED SLIP

Sustainable wet slip resistance* AS/NZS 4586 R10

EN 13845 Esf

RRL Pendulum Test ≥36 (wet test - 4S Rubber/Slider 96)

Surface roughness Rz ≥20µm

The slip resistance across all Polysafe products is assured throughout the guaranteed life of the product, with strict adherence to HSE Guidelines.



ABRASION RESISTANCE

EN 13845 50,000 cycles

EN 649 Group T



VOC EMISSIONS

AgBB VOC test :

Cert No: Z-156 603-523

Floorscore certified

Cert No: SCS-FS-02034



AGRÉMENT ASSURANCE

Polysafe Vogue Ultra has been independently assessed by the British Board of Agrément and product performance is assured for at least 10 years in recommended use areas. With proper maintenance, the appearance, colour and slip resistance will be retained during this period.



ENVIRONMENTALLY PREFERABLE FLOORING

Polysafe Vogue Ultra achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 336) in major use areas such as education and healthcare. Polysafe Vogue Ultra is 100% recyclable and contains recycled material.

A full Environmental Report detailing Polyflor's achievements in areas such as recycling, energy reduction and waste avoidance can be found at www.polyflor.com/environment



ELECTRICAL BEHAVIOUR

(body voltage)

EN 1815 ≤2kV

Classified as 'antistatic'



RESISTANCE TO CHEMICALS

Good resistance to dilute acids and alkalis. Chemical resistance charts available on request.



HYGIENE

Contains antimicrobial agents. Independently tested - inhibits growth of MRSA on flooring. Effective maintenance is most important defence against infection.



APPLICATIONS

Polysafe Vogue Ultra is designed for use in areas where enhanced slip resistance is an important consideration. Typical areas include washrooms, WCs, bar serveries, food preparation areas, changing rooms, laundry and sluice rooms, canteens and institutional applications. For continually wet areas please refer to our Polysafe Hydro range. As with all Polysafe products, Polysafe Vogue Ultra should not have a polish applied.



Polysafe safety flooring ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. For clarification and for information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com. At the date of issue the data presented is correct. However, Polyflor Ltd. reserves the right to make changes which do not adversely affect performance or quality.

* For clarification regarding slip resistance, consult Polyflor.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
TEL: +44 (0)161 767 1111 UK SALES DIRECT: +44 (0)161 767 1122 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM
UK SAMPLE REQUESTS: +44 (0)161 767 2551

James Halstead
FLOORING




POLYFLOR POLYSAFE™ VOGUE ULTRA

SAFETY FLOORING

PERFORMANCE AND PROPERTIES



Refer to BRE Global ratings on www.greenbooklive.com



EN 13845

