






altro




Pewter Grey X2539 X4039



Blue X2541




Moss X2533



Mushroom X2542 X4042



Quarry Red X2560 X4060



Walnut X2586 X4086

Altro Classic 25 is also available in Anvil, shown below

Altro Atlas™ 40 (4.0mm or 3.5mm*)

Heavy duty safety flooring. Available in Anvil and the 4 colours shown above.

*Also available, Atlas 35 (3.5mm) as a non-stock item.



Anvil X2594 X4094

Altro Classic™ 25 / Altro Atlas™ 40



no.1 in
independent field trials

essential collection / safety flooring
Altro Classic 25 / Altro Atlas 40

N.B. Exact colour match with samples cannot be guaranteed.

explore altroism at www.altro.com



Altro Classic 25 is the original slip resistant safety flooring. It is a popular choice providing a durable, slip resistant floorcovering. At 4mm thick, Atlas 40 is the toughest Altro safety flooring. It is suitable for a wide range of heavy duty locations.

Standards and Accreditation

Meets and exceeds the requirements of BS EN 649. BBA 96/3229, Detail Sheet No.3.

Slip Resistance

Greater than or equal to 35; low risk of slipping (UK Slip Resistance Guidelines); R10; DIN 51130. The construction of Altro safety flooring ensures that its slip resistance is maintained throughout the life of the product.

Specification

Format	Classic 25	Atlas 40	Roll
Dimensions	20m x 2.0m	12.5m x 2.0m	(EN426)
Thickness	2.5mm	4.0mm	(EN428)
Weight	2.9kg/m ²	4.5kg/m ²	(EN430)

Performance

Classic 25 and Atlas 40

Indentation	≤0.1mm	(EN433)
Dimensional stability	<0.4%	(EN434)
Flexibility	PASS 20mm	
	mandrel	(EN435)
Colour fastness	>6	(EN20105 BO2: Method 3)
Fire performance	≥8kw/m ²	(EN ISO 9239-1)
	Pass	(EN ISO 11925-2)
	Class B _{fl} s1	(EN13501-1)
Sound absorption	Altro Classic 25	
	- 5dB	(ISO140-8)
	Altro Atlas 40	
	- 7dB	(ISO140-8)
Abrasion wear	Group T	(EN660-2)
Classification	Homogenous	
	Classes 34 & 43	(EN685)

Warranties

Warranty	Altro Classic 25	12 years
	Altro Atlas 40	15 years

(subject to conditions on warranty form attached to every roll of Altro safety flooring).

Life expectancy	Altro Classic 25	20+ years
	Altro Atlas 40	25+ years

(under many traffic conditions, wear is comparable to epoxy and quarry tiles).

Chemicals

Resists	Common dilute acids, alkalis and many organic solvents
Caution	Ketone solvents.

N.B. More information on performance and standards is available in Altro Flooring and Walling brochures or on www.altro.com

Staining

Certain chemicals may cause staining of vinyl. Traffic stain can be caused by oil residue, certain cleaning agents, asphalt and anti-oxidants in some types of rubber. For further information or advice, please contact Altro.

Colour Choice

The colour of Altro safety flooring should be carefully chosen with expected traffic conditions in mind and protective measures, such as the use of barrier matting, should be taken wherever possible.

Biological

Excellent surface antibacterial activity due to bacteriostat incorporation*.

*Please consult Altro Technical Services.

essential collection / safety flooring Altro Classic 25 / Altro Atlas 40 /

our promise to deliver



the highest quality products & services



**Resilient
Flooring
Range of
the Year**
(5th year running)



Materials of Composition

Matrix	High quality vinyl
Inclusions	Aluminium oxide granules - throughout, silicon carbide, quartz - surface layer
Backing	Non-woven polyester/cellulose, glass fibre reinforcement
Wear layer	Altro Classic 25 - 2.5mm Altro Atlas 40 - 4.0mm

Recommended Cleaning Methods



no.1 in independent field trials

Machine or hand scrubbing and AltroClean 44™ or other Altro approved cleaners. Technical advances to Altro safety floors significantly improve their cleaning characteristics. Refer to Altro safety flooring routine

maintenance instructions for comprehensive cleaning advice and chemicals on www.altro.com or contact 01462 707600. N.B. Where maximum slip resistance is not required, AltroGloss™ 211, may be applied (entirely on building owner's responsibility for Health & Safety assessment).

Installation and Maintenance

All installations in accordance with Code of Practice BS 8203:2001, and Altro safety flooring installation instructions.

Joints	All hot-welded
Subfloor	As Code of Practice, with effective DPM where necessary
Adhesives	As recommended in Altro safety flooring installation instructions, the Altro price list or at www.altro.com

N.B. Failure to install and maintain Altro floors in accordance with 'Altro safety flooring installation Instructions' can affect its performance and slip resistance. Floors should be protected from other trades and thoroughly cleaned before handover.

Altro Flooring and Walling Ranges

Products include safety flooring, smooth flooring, resin systems, Mondo rubber, sports flooring, hygienic wall coatings, hygienic PVCu walling and ceiling systems, hygienic doorsets, decorative wall coatings and protective wall coatings. For more information ask for the Altro Flooring and Walling Solutions brochures appropriate to your industry sector, or visit www.altro.com

Sample Specification

The slip resistant vinyl sheet flooring to be Altro safety flooring Classic 25, thickness 2.5mm or Atlas 40, thickness 4.0mm, width 2000mm, colour (.....), as manufactured by Altro. All flooring to be hot-welded and laid according to the manufacturer's instructions with recommended adhesives and sealants.

NBS model specification is available for downloading on www.altro.com or telephone 01462 707600.

Prior to specification please ensure you are referring to the most recent sample card.



To obtain individual samples use the SampleExpress service. Please quote the product range and product name/number. Larger samples are also available but may take a few days.

explore altroism at www.altro.com

Explore Light. Explore Colour.
Explore Mood. At www.altro.com