



CX2001 Light Beige



CX2002 Toffee Brown




CX2003 Brick Red




CX2004 Light Grey




CX2005 Dusky Blue



CX2006 Slate Grey



CX2007 Mid Blue



CX2008 Simply Green



CX2009 Nearly Black

Distributor:

## Altro ContraX™


A whole new perspective on flooring



no.1 in  
Independent field trials

**Worlds together**  
explore altroism at [www.altro.com](http://www.altro.com)

N.B. Exact colour match with samples cannot be guaranteed.



altro

# Altro ContraX™

Altro ContraX is the standard choice for maintaining slip resistance in general circulation areas. It offers exceptional value for money and comes in a range of appealing colours.



no.1 in independent field trials

our promise to deliver



the highest quality products & services



## Standards and accreditation

Meets and exceeds the requirements of BS EN 13845.

## Slip resistance

Greater than or equal to 36; low risk of slipping (UK Slip Resistance Guidelines). The construction of Altro safety flooring ensures that its slip resistance is maintained throughout the life of the product\*.

## Specification

Format	Roll	
Dimensions	20m x 2m	(EN426)
Thickness	2.0mm	(EN428)
Weight	2.2 kg/m <sup>2</sup>	(EN430)

## Performance

Indentation	<0.1mm	(EN433)
Dimensional stability	<0.4%	(EN434)
Flexibility	PASS 20mm mandrel	(EN435)
Colour fastness	>6	(EN 20105 BO2: Method 3)
Fire performance	Class 1	
	Bfl s1	(EN13501-1)
	≥8kW/m <sup>2</sup>	(EN ISO9239-1)
	Pass	(EN ISO11925-2)
Abrasion wear	Pass	(EN425)
Classification	Classes 34 & 43	(EN685)
	Heterogenous	

## Warranties

Warranty	5 years
Life expectancy	10+ years

(under many traffic conditions, wear is comparable to epoxy and quarry tiles).

## Chemicals

Resists	Common dilute acids, alkalis and many organic solvents
Caution	Ketone solvents

N.B. More information on performance and standards is available in the Altro Flooring and Walling brochure or at [www.altro.com](http://www.altro.com)

## Staining & protection

Certain chemicals may cause staining of vinyl. Traffic stain can be caused by oil residue, certain cleaning agents, asphalt and anti-oxidants in some types of rubber. Cigarette ends will scar the surface of vinyl floor coverings. Chairs and stools should be fitted with quality plastic feet to avoid damage. For further information or advice, please contact Altro.

## Colour choice

The colour of Altro safety flooring should be carefully chosen with expected traffic conditions in mind. Protective measures, such as the use of barrier matting, should be taken wherever possible.

## Biological

Excellent surface antibacterial activity due to bacteriostat incorporation\*\*.

\*\*Please consult Altro for more information.

## Materials of composition

Matrix	High quality vinyl
Inclusions	Silicon carbide and coloured quartz surface layer
	Non-woven polyester/cellulose, glass fibre reinforcement
Wear layer	1.0mm

## Recommended cleaning methods

Machine or hand scrubbing and AltroClean 44™. Technical advances to Altro safety floors significantly improve their cleaning characteristics. Refer to Altro safety flooring routine maintenance commercial or domestic instructions for comprehensive cleaning advice and chemicals on [www.altro.com](http://www.altro.com) or contact 01462 707600.

## Installation and maintenance

All installations in accordance with Code of Practice BS 8203:2001, and Altro safety flooring installation instructions.

Joints	All hot-welded
Subfloor	As Code of Practice, with effective DPM where necessary
Adhesives	As recommended in Altro safety flooring installation instructions, the Altro price list or visit <a href="http://www.altro.com">www.altro.com</a>

N.B. Failure to install and maintain Altro flooring in accordance with 'Altro safety flooring installation instructions' can affect its performance and slip resistance. Floors should be protected from other trades and thoroughly cleaned before handover.

## Altro flooring and walling ranges

Products include safety flooring, smooth flooring, resin systems, Mondo rubber, sports flooring, hygienic wall coatings, hygienic PVCu walling and ceiling systems, hygienic doorsets, decorative wall coatings and protective wall coatings. For more information ask for the Altro Flooring and Walling Solutions brochures appropriate to your industry sector, or visit [www.altro.com](http://www.altro.com)

## Sample specification

The slip resistant vinyl sheet flooring to be Altro safety flooring ContraX, thickness 2.0mm, width 2000mm, colour (.....), as manufactured by Altro. All flooring to be hot welded and laid according to the manufacturer's instructions with recommended adhesives and sealants.

NBS model specification is available for downloading on [www.altro.com](http://www.altro.com) or telephone 01462 707600.

Prior to specification please ensure you are referring to the most recent sample card.



[samples@altro.com](mailto:samples@altro.com)

To obtain individual samples use the SampleExpress service. Please quote the product range and product name/number. Larger samples are also available but may take a few days.

\*For wet areas where bare foot slip resistance is required such as shower and drying off areas, swimming pool and whirlpool surrounds and their changing rooms we recommend the use of Altro T20 Marine.



Supporting the HSE in their 2010 goals to reduce slips and trips

explore altroism at [www.altro.com](http://www.altro.com)

Altro Limited, Works Road, Letchworth Garden City, Hertfordshire SG6 1NW. Tel: 01462 707600 Fax: 01462 707515 e-mail: [enquiries@altro.com](mailto:enquiries@altro.com)  
Altro, Altro ContraX, AltroClean and SampleExpress are trademarks of Altro Limited.

altro